



NPH3.2-12FR


Sealed Rechargeable
Lead-Acid Battery

12V, 3.2Ah

Specifications


- **NOMINAL VOLTAGE:** 12V
- **NOMINAL CAPACITY:**
 - 10 hr. rate of 0.32A to 10.50V 3.2Ah
 - 5 hr. rate of 0.58A to 10.20V 2.9Ah
 - 1 hr. rate of 2.4A to 9.60V 2.4Ah
- **WEIGHT (approx.):** 3.09 pounds (1.40 kgs.)
- **ENERGY DENSITY (10 hr. rate):** 1.16 WH/cubic inch (71 WH/liter)
- **SPECIFIC ENERGY (10 hr. rate):** 12.6 WH/pound (28 WH/kg)
- **INTERNAL RESISTANCE OF CHARGED BATTERY:** 35 milliohms (approx.)
- **MAXIMUM DISCHARGE CURRENT WITH STANDARD TERMINALS:** 40 amperes
- **MAXIMUM SHORT-DURATION DISCHARGE CURRENT:** 100 amperes
- **OPERATING TEMPERATURE RANGE:**
 - CHARGE 5°F to 122°F (-15°C to 50°C)
 - DISCHARGE -4°F to 140°F (-20°C to 60°C)
- **CHARGE RETENTION (shelf life) at 68°F (20°C):**
 - 1 month 97%
 - 3 months 91%
 - 6 months 85%
- **LIFE EXPECTANCY:**
 - STANDBY USE 3 to 5 years
 - CYCLE USE (approx.):
 - 100% depth of discharge 250 cycles
 - 50% depth of discharge 550 cycles
 - 30% depth of discharge 1200 cycles
- **SEALED CONSTRUCTION:** Can be operated in any position without leakage.
- **STANDARD TERMINAL:** Quick Disconnect .187
- **HOUSING MATERIAL:** Container and cover made from Flame Retardant ABS (UL94-V0/L.O.I.>28%)

Dimensions



DIMENSIONS: MM (INCHES)

Terminal



DIMENSIONS: INCHES


UL listing pending - File No MH16464




EnerSys™

Power/Full Solutions


DISCHARGE CHARACTERISTIC CURVES AT 25°C (77°F)




TEMPERATURE EFFECTS IN RELATION TO BATTERY CAPACITY




SELF DISCHARGE CHARACTERISTICS




OPEN CIRCUIT VOLTAGE VS REMAINING CAPACITY



CYCLE SERVICE LIFE IN RELATION TO DEPTH OF DISCHARGE



FLOAT SERVICE LIFE



When the battery will be used by current in excess of 3C, consult with EnerSys prior to use.

CHARGING METHODS (At 20°C)

Cycle use: Maximum charging current 0.80A
 Charging voltage 14.4 to 15.0V
Standby use: Float charging voltage 13.50 to 13.80V

CAUTION

- Avoid short circuit.
- Do not charge in a sealed container.



EnerSys
 P.O. Box 14145
 Reading, PA 19612-4145
 USA
 Tel: +1-610-208-1991
 +1-800-538-3627

EnerSys EMEA
 Brussels, Belgium
 Tel: +32 (0)2 247 94 47
EnerSys Asia
 Guangdong, China
 Tel: +86 755 2689 3639

Represented by:

Printed in U.S.A.
 © 2006 EnerSys. All rights reserved.
 Trademarks and logos are the property of EnerSys and its affiliates unless otherwise noted.